



# CHINMORE INDUSTRY CO.,LTD

## Specification

1. Cable Assembly with RF Connector
2. Chinmore's No: CX-MMCX174SMA-097
3. Frequency: 1~3GHz
4. VSWR: 2.0:1
5. Cable: RG-174 150mm
6. Connector: SMA F(BH) & RA MMCX M

✧RoHS Compliant

✧ISO 9001 & ISO 14001

Cable	RG174/U	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>ROHS</b>            ISO 9001            ISO 14001         </div>
OD	∅2.7±0.15mm	
Cover	Black	
MMCX 90° M	Gold<鍍金>	
SMA(BH)F	Gold<鍍金>	

  
  

Material:		Treatment:		竣茂工業有限公司 Chinmore Industry CO.,LTD			
Drawer	Design	Apror	Tolerance	Unit:	mm	TITLE	MMCX 90° M+174U+SMA(BH)F
		公差 X=±0.5 Y=±0.2 Z=±0.1 XXX=±0.05		Ver:	A	Scale	1:1
Part NO	CX-MMCX174SMA-097	File NO:	QR0402	Drawing NO	100-23026-008		

Frequency (MHz)	VSWR	Insertion Loss (dB)
1000	1.07	-0.34
2000	1.36	-0.69
3000	1.09	-0.68

TEST Report



